



Preface

The purpose of this document is to enable the support for multiple iBrowse installations on multiple domains in one IIS server.

Environment: TKSQl only

Installation: Defining the IBROWSE.INI.

Defining the IBROWSE.INI file:

The IBROWSE.INI file is located inside the "WINDOWS" folder on the IIS server.

The definitions for each site will be added at the end of the iBrowse.ini file under sections which their header will be the active site's name. (the Virtual directory name).

Under each section the only parameters that will be defined are the parameters that are differ from the default parameters under the [SYS_PARAM] section.



Note: A parameter that is not exist under a section will be taken from the default [SYS_PARAM] section.

The allowed parameters are:

DATA_SOURCE
DATA_BASE
DATA_PATH
SQL_PARAM
PARENT_PAGE
MAGNET_CARD
START_PAGE

A screenshot of a Notepad window titled "IBROWSE.INI - Notepad". The window shows the contents of the IBROWSE.INI file, which is divided into three sections: [SYS_PARAM], [IBROWSE_X], and [IBROWSE_Y]. The [SYS_PARAM] section contains default values for Data_Source, DATA_BASE_TYPE, DATABASE, DATA_PATH, LANGUAGE, and SQL_PARAM. The [IBROWSE_X] and [IBROWSE_Y] sections contain values for Data_Source, DATABASE, DATA_PATH, SQL_PARAM, PARENT_PAGE, and MAGNET_CARD, with some values being empty or different from the defaults.

```
IBROWSE.INI - Notepad
File Edit Format View Help

[SYS_PARAM]
Data_Source=david_tuchman
DATA_BASE_TYPE=0
DATABASE=IBSQL
DATA_PATH=d:\tksql_new\stam
LANGUAGE=HEBREW
SQL_PARAM=052666769211DF3B1F9FBBDD583E4B7C8083DD925

[IBROWSE_X]
Data_Source=X
DATABASE=X
DATA_PATH=d:\tksql_newx\stam
SQL_PARAM=
PARENT_PAGE=
MAGNET_CARD=

[IBROWSE_Y]
Data_Source=Y
DATABASE=Y
DATA_PATH=d:\tksql_newy\stam
SQL_PARAM=
PARENT_PAGE=
MAGNET_CARD=
```